# **MARKLAND**

# i-Ark

## **80M**

### **Professional Identity Verification Station**



i-Ark M08 is a professional mobile identity verification workstation. Weighing less than 23kg with a compact suitcase design, it ensures effortless mobility for field operations.

The i-Ark M08 is a fully functional workstation, not merely a storage case. Deployable within 1 minute, enabling smooth transitions between mobile and operational modes. This all-in-one solution acquires, stores, and transmits citizens biometric data, operating reliably in remote areas without internet or power. Pre-integrated devices eliminate additional configurations, enhancing efficiency. The swappable battery extends runtime.

Primary Applications: Elections, national ID registration/verification, card issuance, population census, refugee registration, KYC, etc.

#### **Configuration Components**

• Fingerprint Scanner: IB four-finger scanner supporting flat (ten-finger/single finger) and rolled (single-finger) capture. FBI

certified

• Document Reader: Combines MRZ reading, NFC technology, ISO7816 compliance, plus QR/bar/PDF417 scanning capabilities.

• **Printer:** Standard A4 thermal printer (300DPI).

• Signature Pad: Passive wireless electromagnetic induction technology replicates natural pen-on-paper writing

experience.

• Document Scanner: Professional scanner for long-page documents and environment-resistant processing.

• Camera: Binocular lens design captures simultaneous natural/IR images; features liveness detection, auto-focus,

5MP resolution, wide dynamic range fill light, auto white balance, and color correction.

• Iris Scanner: CMITECH BMT-20 binoculars-type iris biometric imager.



| Parameter   |                           | Details  |
|---|---------------------------|--|
| Laptop  | Model (Optional)          | ThinkPad S2  |
|   | CPU Model                 | R5-7530U   |
|   | Screen Size               | 13.3 inches  |
|   | Resolution                | 1920X1080  |
|   | Storage                   | 512GB SSD  |
|   | RAM                       | 16GB   |
| 4-4-2<br>Fingerprint Scanner                      | Brand                     | IB   |
|   | Model                     | KJ210DA-E00  |
|   | Liveness Detection        |  |
|   |                           | Supported  |
|   | Sensor                    | TFT SOODDI/FDL JAACKD JIS N  |
|   | Resolution                | 500DPI (FBI and MOSIP certified)   |
|   | Supported Formats         | JPG2000, BMP, PNG, WSQ (FBI-certified)   |
| Thermal Printer                                   | Paper Width               | A4   |
|   | Print Density             | 300DPI   |
| Camera  | Sensor                    | Binocular  |
|   | Resolution                | 5 Megapixel  |
|   | Autofocus                 | Supported  |
|   | Output Formats            | JPG, MJPG  |
| Document Scanner                                  | Туре                      | A4 duplex color high-speed sheet-fed embedded scanner  |
|   | Resolution                | 600 x 600 DPI  |
|   | Light Source              | LED  |
|   | Color Depth               | Input 48-bit (color )/16-bit (grayscale); Output 24-bit/8-bit                                |
|   | Scan Area                 | Max 216x594 mm; Min 88x54 mm   |
|   | Output Formats            | JPG, BMP, multi-page TIFF/PDF  |
|   | Scan Speed                | 2 seconds per page (duplex, color mode, 300DPI, A4)  |
| Document reader<br>( MRZ + NFC + Contact<br>+ QR) | Supported Documents       | ICAO 9303-compliant (TD1/2/3 )   |
|   | Light Source              | Near-infrared (B900, 860nm)  |
|   | Contact Smart Card Reader | ISO/IEC 7816 Part 1 – 4s   |
|   |                           | ISO 7816 smart card Class A/B/C  |
|   | NFC Reader                | ISO/IEC 14443 A/B Part 1 - 4   |
|   |                           | ISO18092   |
|   | QR Code Support           | Code 39, Code 32, Code 128, UPC/EAN/JAN, Code 93, Interleaved 2 of 5, Codabar, Matrix 2 of 5 |
|   |                           | Industrial 2 of 5  |
|   |                           | QR Code, Data Matrix, Aztec Code, PDF417, etc.   |
| Signature Pad                                     | Screen Size               | 5 inches   |
|   | Display                   | TFT LCD  |
|   | Aspect Ratio              | 16:9   |
|   | Active Area               | 108x64.8 mm  |
|   | Resolution                | 800x480  |
|   | Brightness                | 300 cd/m2  |
|   | Response Time             | 15 ms  |
|   | Viewing Angle             | 140° (H)/120° (V), CR≥10   |
| Power Supply                                      | Capacity                  | 32,000 mAh (swappable)   |
| Iris Scanner                                      | Capture Distance          | 18.4 - 20 pixels/mm  |
|   | Image Size per iris       | 640x480  |
|   | Standard                  | ISO/IEC 19794-6  |
|   | Light Source              | Infrared   |
|   | Eye Safety                | IEC 62471, IEC 60825-1   |
|   | Certifications            | STQC, MOSIP  |

<sup>\*</sup>TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.